

# XA3300, XA4000, XA5000 APPLICATOR



## INNOVATION FROM WITHIN

### Setting the new standard in Hydroseeding Applicators

- 173Hp Cummins Tier 4 Final Engine
- First of its kind, "Power Pack", design that is removable, replaceable and upgradable
- Innovatively designed hydraulic cooling package; decreases maintenance costs
- Corrosion reducing materials on tank top, working platform and ladder
- Fully enclosed engine compartment
- Twin, variable speed hydraulic agitators
- 6" x 3" vortex pump with single bend suction line
- Raised loading hatch

STAINLESS STEEL  
MIXING TANKS

POWERFUL VARIABLE SPEED  
HYDRAULIC AGITATION

INNOVATIVE "POWER  
PACK" DESIGN

INDUSTRY EXCLUSIVE "5 POINT"  
AGITATOR SEAL ASSEMBLY

[APEXSEEDER.COM](http://APEXSEEDER.COM)

# SPECS



<b>Engine</b>	Cummins QSB 4.5 turbo charged, water cooled diesel. Tier 4 (173hp) compliant engine with self diagnostics including engine shut off due to low oil pressure or high engine temperature
<b>Pump</b>	6" x 3" Vortex Pump - single bend 6" suction line
<b>Agitation</b>	Twin, variable speed (0-150 rpm) hydraulically driven agitators
<b>Standard Features</b>	<ul style="list-style-type: none"> <li>· 3-16" stainless steel</li> <li>· Military grade aluminum tank top</li> <li>· Military grade aluminum rails</li> <li>· Raised loading hatch - 20" (51cm)</li> <li>· Fully integrated 80 gallon fuel tank</li> <li>· Exclusive 5 point agitator seal assembly</li> <li>· Fully enclosed engine compartment</li> <li>· Three large swing gates</li> <li>· Liquid recirculation</li> </ul>
<b>Nozzles</b>	Complete set of 6 nozzles - long distance, narrow and wide ribbon fan - high and low volume
<b>Optional Equipment</b>	Hydraulically operated hose reel with 200' of 1-1/4" hose with Air Flush Dual 3" discharge booms
<b>Max Discharge Distance</b>	Up to 325' (99 meters)

	<b>XA3300</b>	<b>XA4000</b>	<b>XA5000</b>
<b>Tank: Liquid Capacity</b>	3,260 gal / 12,370 l	3,950 gal / 14,952 l	4,740 gal / 17,943 l
<b>Working Capacity</b>	2,930 gal / 11,091 l	3,560 gal / 13,476 l	4,270 gal / 16,164 l
<b>Materials Capacity</b>			
<b>Granular Solids</b>	12,000 lb / 5,443 kg	14,800 lb / 6,713 kg	18,600 lb / 8,437 kg
<b>Fiber Mulch</b>	1,800 lb / 816 kg	2,150 lb / 975 kg	2,700 lb / 1,225 kg
<b>Empty Weight</b>	11,060 lb / 5,016 kg	12,000 lb / 5,443 kg	13,480 lb / 6,114 kg
<b>Approx. Working Weight</b>	37,140 lb / 16,846 kg	43,600 lb / 19,777 kg	51,400 lb / 23,315 kg
<b>Length</b>	19' 0.8"	22' 2.8"	26' 0.6"
<b>Width</b>	8' 3.5"	8' 3.5"	8' 3.5"
<b>Height</b>	9' 0.0"	9' 0.0"	9' 0.0"

\*Weights are approximate and do not include any stowed materials.

## Erosion Control Products Corporation

9599 Nanticoke Business Park Dr.  
Greenwood, DE 19950  
513-642-0147

**APEXSEEDER.COM**