

XA1200

APPLICATOR



INNOVATION FROM WITHIN

Setting the new standard in Hydroseeding Applicators

- Stainless Steel mixing tank
- Military grade aluminum tank top
- Fully enclosed engine compartment with service doors
- 2 large slide gates
- Raised loading hatch
- Modular "Power Pack" design
- Bolt-on 37 gallon fuel tank
- 42 gallon hydraulic tank
- 34" Mounting rail legs for direct truck frame mounting



STAINLESS STEEL
MIXING TANK

TIER 4
DOOSAN ENGINE

INDUSTRY EXCLUSIVE "5 POINT"
AGITATOR SEAL ASSEMBLY

APEXSEEDER.COM

SPECS

Engine	Doosan D24: 74 hp. (55kW). Turbocharged, water cooled, Tier 4 Final with self diagnostics
Pump	4" x 2" APEX engineered Vortex Pump, hydraulically driven with variable speed control
Agitation	Single Shaft, 15 blades, hydraulically driven, reversible, variable speed (0-130 rpm), with liquid recirculation and APEX exclusive 5 Point Seal Assembly
Standard Features	<ul style="list-style-type: none">• Stainless Steel mixing tank• Military grade aluminum tank top• Fully enclosed engine compartment with service doors• 2 large slide gates• Raised loading hatch• Modular "Power Pack" design• Bolt-on 37 gallon fuel tank• 42 gallon hydraulic tank• 34" Mounting rail legs for direct truck frame mounting
Nozzles	3 nozzles- wide fan, narrow fan & long distance
Optional Equipment	Hose reel with 1-1/4"X200' (31.75mm x 60.96m) semi-rigid hose & remote valve
Max Discharge Distance	185 feet (57 m)

*Weights are approximate and do not include any stowed materials.