

XA1200

APPLICATOR



INNOVATION FROM WITHIN

Setting the new standard in Hydroseeding Applicators

- Stainless Steel mixing tank
- Military grade aluminum tank top
- Fully enclosed engine compartment with service doors
- 2 large slide gates
- Raised loading hatch
- Modular "Power Pack" design
- Bolt-on 37 gallon fuel tank
- 42 gallon hydraulic tank
- 34" Mounting rail legs for direct truck frame mounting



STAINLESS STEEL
MIXING TANK

TIER 4
DOOSAN ENGINE

INDUSTRY EXCLUSIVE "5 POINT"
AGITATOR SEAL ASSEMBLY

APEXSEEDER.COM

SPECS

Engine	Doosan D24: 74 hp. (55kW). Turbocharged, water cooled, Tier 4 Final with self diagnostics
Pump	4" x 2" APEX engineered Vortex Pump, hydraulically driven with variable speed control
Agitation	Single Shaft, 15 blades, hydraulically driven, reversible, variable speed (0-130 rpm), with liquid recirculation and APEX exclusive 5 Point Seal Assembly
Standard Features	<ul style="list-style-type: none"> · Stainless Steel mixing tank · Military grade aluminum tank top · Fully enclosed engine compartment with service doors · 2 large slide gates · Raised loading hatch · Modular "Power Pack" design · Bolt-on 37 gallon fuel tank · 42 gallon hydraulic tank · 34" Mounting rail legs for direct truck frame mounting
Nozzles	3 nozzles- wide fan, narrow fan & long distance
Optional Equipment	Hose reel with 1-1/4"X200' (31.75mm x 60.96m) semi-rigid hose & remote valve
Max Discharge Distance	185 feet (57 m)

	SKID (XA 1200-S)	STRAIGHT TOW (XA1200-T)	GOOSENECK TOW (XA1200-GN)
Tank			
--Liquid Capacity	1,200 gal / 4,542 L	1,200 gal / 4,542 L	1,200 gal / 4,542 L
--Working Capacity	1,080 gal / 4,088 L	1,080 gal / 4,088 L	1,080 gal / 4,088 L
Materials Capacity			
--Granular Solids	3,500 lb / 1,588 kg	3,500 lb / 1,588 kg	3,500 lb / 1,588 kg
--Fiber Mulch	500 lb / 227 kg	500 lb / 227 kg	500 lb / 227 kg
Empty Weight	5,260 lb / 2,386 kg	7,100 lb / 3,221 kg	7,700 lb / 3,493 kg
Approx. Working Weight	15,220 lb / 6,903 kg	16,000 lb / 7,257 kg	17,660 lb / 8,010 kg
Length	186" / 4.74 m	256" / 6.50 m	283" / 7.19 m
Width	72" / 1.83 m	72" / 1.83 m	72" / 1.83 m
Height	88" / 2.24 m	106" / 2.69 m	110" / 2.79 m

*Weights are approximate and do not include any stowed materials.