

XA1200

# APPLICATOR



## INNOVATION FROM WITHIN

### Setting the new standard in Hydroseeding Applicators

- Stainless Steel mixing tank
- Military grade aluminum tank top
- Fully enclosed engine compartment with service doors
- 2 large slide gates
- Raised loading hatch
- Modular "Power Pack" design
- Bolt-on 37 gallon fuel tank
- 42 gallon hydraulic tank
- 34" Mounting rail legs for direct truck frame mounting

STAINLESS STEEL  
MIXING TANK

TIER 4 HYUNDAI  
ENGINE

INDUSTRY EXCLUSIVE "5 POINT"  
AGITATOR SEAL ASSEMBLY

[APEXSEEDER.COM](http://APEXSEEDER.COM)

# SPECS

<b>Engine</b>	Hyundai D24: 74 hp. (55kW). Turbocharged, water cooled, Tier 4 Final with self diagnostics
<b>Pump</b>	4" x 2" APEX engineered Vortex Pump, hydraulically driven with variable speed control
<b>Agitation</b>	Single Shaft, 15 blades, hydraulically driven, reversible, variable speed (0-130 rpm), with liquid recirculation and APEX exclusive 5 Point Seal Assembly
<b>Standard Features</b>	<ul style="list-style-type: none"> <li>· Stainless Steel mixing tank</li> <li>· Military grade aluminum tank top</li> <li>· Fully enclosed engine compartment with service doors</li> <li>· 2 large slide gates</li> <li>· Raised loading hatch</li> <li>· Modular "Power Pack" design</li> <li>· Bolt-on 37 gallon fuel tank</li> <li>· 42 gallon hydraulic tank</li> <li>· 34" Mounting rail legs for direct truck frame mounting</li> </ul>
<b>Nozzles</b>	3 nozzles- wide fan, narrow fan & long distance
<b>Optional Equipment</b>	Hose reel with 1-1/4"X200' (31.75mm x 60.96m) semi-rigid hose & remote valve
<b>Max Discharge Distance</b>	185 feet (57 m)

	SKID (XA 1200-S)	STRAIGHT TOW (XA1200-T)	GOOSENECK TOW (XA1200-GN)
<b>Tank</b>			
--Liquid Capacity	1,200 gal / 4,542 L	1,200 gal / 4,542 L	1,200 gal / 4,542 L
--Working Capacity	1,080 gal / 4,088 L	1,080 gal / 4,088 L	1,080 gal / 4,088 L
<b>Materials Capacity</b>			
--Granular Solids	3,500 lb / 1,588 kg	3,500 lb / 1,588 kg	3,500 lb / 1,588 kg
--Fiber Mulch	500 lb / 227 kg	500 lb / 227 kg	500 lb / 227 kg
Empty Weight	5,260 lb / 2,386 kg	7,100 lb / 3,221 kg	7,700 lb / 3,493 kg
Approx. Working Weight	15,220 lb / 6,903 kg	16,000 lb / 7,257 kg	17,660 lb / 8,010 kg
Length	186" / 4.74 m	256" / 6.50 m	283" / 7.19 m
Width	72" / 1.83 m	72" / 1.83 m	72" / 1.83 m
Height	88" / 2.24 m	106" / 2.69 m	110" / 2.79 m

\*Weights are approximate and do not include any stowed materials.